IN THE CLAIMS:

Please cancel claims 1-11 without prejudice and amend the claims as follows:

1. (Canceled) A system comprising:

a service processor controlled by operating software;

a plurality of system resources controlled by said service processor;

an uninterruptible power supply (UPS) connected to at least one system

resource; and

a memory for storing a configuration file that lists said plurality of system

resources and said UPS;

wherein said service processor uses said configuration file to determine what

system resources are connected to said UPS.

2. (Canceled) A system according to claim 1, wherein said at least one system

resource includes redundant first and second power supplies, and wherein said service

processor initiates a warning if said UPS connects to both said first and second power

supplies.

3. (Canceled) A system according to claim 2, further including a first AC power

line and a second AC power line, wherein said UPS is powered by said first AC power

line; wherein said configuration file lists operative connections between said first and

second power supplies and said first and second AC power lines, and wherein said

service processor determines if said first and second power supplies are operatively

connected to the same AC power line.

4. (Canceled) A system according to claim 3, wherein said first AC power line and

said second AC power line are connected to different circuit-breakers.

App. Ser. No.: 10/687,438 Atty. Dkt. No. ROC920030181US1

PS Ref. No.: IBMK30181

5. (Canceled) A system according to claim 1, wherein said UPS is for notifying said service processor of an impending power failure, and wherein said service processor can perform a controlled shutdown of said at least one system resource when notified of an impending power failure.

6. (Canceled) A system comprising:

a service processor controlled by operating software;

an uninterruptible power supply (UPS) for supplying AC power and UPS identifying information on a power connection; and

a plurality of system resources for sensing said identifying information and for sending said identifying information to said service processor;

wherein said service processor receives and examines identifying information to determine which system resources are connected to said UPS.

- 7. (Canceled) A system according to claim 6 wherein said identifying information is an IP address.
- 8. (Canceled) A system according to claim 6 wherein said identifying information is a serial number.
- 9. (Canceled) A system according to claim 6, wherein at least one system resource includes redundant first and second power supplies, and wherein said service processor determines if said first and second power supplies are both connected to said UPS.
- 10. (Canceled) A system according to claim 9, wherein said service processor initiates a warning if said UPS connects to both said first and second power supplies.
- 11. (Canceled) A system according to claim 6, wherein said UPS notifies said service processor of an impending power failure, and wherein said service processor

App. Ser. No.: 10/687,438 Atty. Dkt. No. ROC920030181US1

PS Ref. No.: IBMK30181

performs a controlled shutdown of system resources connected to said UPS in response to said notification.

12. (Original) A system comprising:

a service processor controlled by operating software having power microcode;

an uninterruptible power supply (UPS) for supplying AC power on a power connection, wherein said UPS adjusts said AC power under control of said power microcode;

a plurality of system resources that can sense an out-of-range condition on their power inputs, wherein said power input of at least one system resource is connected to said power connection, and wherein said plurality of system resources notifies said service processor when an out of range condition occurs;

wherein said service processor sends power microcode to said UPS that causes said UPS to produce AC power having an out-of-range condition; and

wherein said service processor receives and examines notifications of out-ofrange conditions to determine what system resource is connected to said UPS.

- 13. (Currently Amended) [[A]] <u>The</u> system according to claim 12 wherein said power microcode causes said AC power voltage to increase.
- 14. (Currently Amended) [[A]] <u>The</u> system according to claim 12 wherein said power microcode causes said AC power voltage to decrease.
- 15. (Currently Amended) [[A]] <u>The</u> system according to claim 12 wherein said power microcode causes said AC power to turn off.
- 16. (Currently Amended) [[A]] <u>The</u> system according to claim 12 wherein said power microcode causes said UPS to vary said power AC power such that said power AC power achieves an out-of-range condition and then achieves an in-range condition.

App. Ser. No.: 10/687,438 Atty. Dkt. No. ROC920030181US1

PS Ref. No.: IBMK30181

17. (Currently Amended) [[A]] <u>The</u> system according to claim 16 wherein said service processor correlates power microcode commands and said out-of-range condition and said in-range condition to verify that said power microcode commands caused said out-of-range condition.

- 18. (Currently Amended) [[A]] <u>The</u> system according to claim 12 wherein at least one system resource includes redundant first and second power supplies, and wherein said service processor initiates a warning if said first and second power supplies are both connected to said UPS.
- 19. (Currently Amended) [[A]] <u>The</u> system according to claim 18, further including a first AC power line and a second AC power line, wherein said UPS is connected to said first AC power line; and wherein said second power supply is operatively connected to said second AC power line.
- 20. (Currently Amended) [[A]] <u>The</u> system according to claim 12, wherein said UPS can notify said service processor of an impending power failure, and wherein said service processor can perform a controlled shutdown of system resources connected to said UPS when notified of an impending power failure.